





ENTEC® 26 EuroChem Agro GmbH

(83010094)



3,6mm





















0,97kg/l

Kalibrierfaktor

0,96

Wurfweitenparameter

16

ZA-TS / ZG-TS															
															
TS 1	15.0	43	720	A	1	720	1	19	500	1	29	400	23	-5	240
	16.0	43	720	A	1	720	1	18	500	1	28	400	23	-5	240
	18.0	43	720	A	1	720	1	17	600	1	27	500	23	-5	240
	20.0	43	800	A	1	800	1	17	600	1	27	500	25	-4	227
	21.0	43	800	A	1	800	1	16	600	1	26	500	25	-3	227
	24.0	45	800	A	1	800	1	15	720	1	25	600	25	-1	247
TS 2	24.0	9	720	B	3	800	3	17	720	3	27	600	27	-2	183
	27.0	10	720	D	X	600	1	16	720	1	26	600	27	0	193
	28.0	12	720	D	X	600	1	15	720	1	25	600	28	0	213
	30.0	15	900	D	X	720	1	15	800	1	25	720	33	-2	197
	32.0	16	900	D	X	800	1	16	900	1	26	800	33	0	207
	33.0	16	900	D	X	800	1	15	900	1	25	800	33	0	207
	36.0	22	900	D	X	800	1	15	900	1	25	800	34	3	267
TS 3	24.0	12	720	C	2	800	2	17	720	2	27	600	31	-5	199
	27.0	13	720	C	3	800	3	16	720	3	26	600	32	-4	209
	28.0	13	720	C	3	800	3	15	720	3	25	600	31	-3	209
	30.0	15	800	C	3	900	3	15	800	3	25	720	34	-3	190
	32.0	16	800	C	3	900	3	15	800	3	25	720	34	-2	200
	33.0	16	800	C	3	900	3	14	800	3	24	720	34	-1	200
	36.0	17	900	D	X	720	1	14	800	1	24	720	36	0	200
	39.0	22	900	D	X	800	1	14	900	1	24	800	38	2	250
	40.0	23	900	D	X	800	1	13	900	1	23	800	38	2	220
	42.0	26	900	D	X	800	1	13	900	1	23	800	39	3	254