














(83021189)

**Patentkali® 30%K₂O, 10%MgO, 42%SO₃ K+S Kali GmbH
[nl]**

 **3.30mm**  **1.23 kg/l**



ZAX						
						
Omnia-Set XPerfect	10	7 / 39	720	9	12	14
	12	7 / 39	720	7	10	12
	15	8 / 40	720	4	8	10
	16	8 / 40	720	3	6	9
	18	10 / 40	720	1	5	8



Breite		kg / ha																								
		50	75	100	125	150	175	200	225	250	275	300	325	350	375	400	425	450	475	500	550	600	700	800	900	1000
10	10	8	9	9,5	10	10,5	11	11,5	12	12	12,5	13	13,5	14	14,5	14,5	15	15,5	16	16,5	17,5	18	20	22	24	26,5
	12	8,5	9,5	10	10,5	11	11,5	12	12,5	13	13,5	14	14,5	15	15,5	16	16,5	17	17,5	18	19,5	20,5	23	25,5	28,5	-
	14	9	9,5	10,5	11	11,5	12	12,5	13,5	14	14,5	15	15,5	16	17	17,5	18	18,5	19,5	20	21,5	23	26	29	-	-
12	10	8,5	9,5	10	10,5	11	11,5	12	12,5	13	13,5	14	14,5	15	15,5	16	16,5	17	17,5	18	19,5	20,5	23	25,5	28,5	-
	12	9	9,5	10,5	11	11,5	12	13	13,5	14	14,5	15,5	16	16,5	17	17,5	18,5	19	19,5	20,5	22	23,5	26,5	30	-	-
	14	9	10	11	11,5	12	13	13,5	14,5	15	16	16,5	17	18	18,5	19,5	20,5	21	22	23	24,5	26,5	-	-	-	-
15	10	9	10	10,5	11	12	12,5	13	13,5	14,5	15	15,5	16	17	17,5	18	19	19,5	20,5	21	22,5	24	27,5	-	-	-
	12	9,5	10	11	12	12,5	13,5	14	15	15,5	16,5	17	18	18,5	19,5	20,5	21,5	22	23	24	26	28,5	-	-	-	-
	14	9,5	10,5	11,5	12,5	13,5	14	15	16	17	18	18,5	19,5	20,5	22	23	24	25	26,5	27,5	30	-	-	-	-	-
16	10	9	10	10,5	11,5	12	12,5	13,5	14	14,5	15,5	16	17	17,5	18	19	19,5	20,5	21	22	23,5	25,5	29	-	-	-
	12	9,5	10,5	11	12	13	13,5	14,5	15,5	16	17	17,5	18,5	19,5	20,5	21,5	22,5	23,5	24,5	25,5	28	30	-	-	-	-
	14	10	11	12	12,5	13,5	14,5	15,5	16,5	17,5	18,5	19,5	20,5	21,5	23	24	25,5	26,5	28	29	-	-	-	-	-	-
18	10	9,5	10	11	12	12,5	13,5	14	15	15,5	16,5	17	18	18,5	19,5	20,5	21,5	22	23	24	26	28,5	-	-	-	-
	12	9,5	10,5	11,5	12,5	13,5	14,5	15,5	16	17	18	19	20	21	22	23,5	24,5	26	27	28,5	-	-	-	-	-	-
	14	10	11	12	13,5	14,5	15,5	16,5	17,5	18,5	20	21	22,5	24	25	26,5	28	29,5	-	-	-	-	-	-	-	-

	Arbeitsbreite
	Streuschaufelpositionen
	Streuscheibendrehzahl
	Randstreuen
	Grenzstreuen
	Grenzgrabenstreuen
	Limiter
	Kalibrierfaktor
	Durchmesser
	Schüttdichte

Zapfwelle	1 : 1.33	Streuscheibendrehzahl
375		500
415		550
450		600
540		720
600		800
650		870
675		900
750		1000